



Advanced Applications

Material Safety Data Sheet

Version Number: 1

Address: Advanced Materials  
75 Tilbury Road  
Salem, NJ 08079

Effective Date: June 2004

24 Hour Emergency Assistance: (856) 935-1400

---

## **Raprex™ R-300A1**

---

### **SECTION 1 - CHEMICAL PRODUCT IDENTIFICATION**

- |     |   |  |
|-----|---|--|
| 1a. | Trade Name  | Raprex™ R-300A1  |
| 1b. | This MSDS applies to the product codes listed in this section | R-300A1  |
| 1c. | Chemical Name/Synonyms  | Polymer of Ethylene and Octene and Product Stabilizers |
- 

### **SECTION 2 - COMPOSITION INFORMATION**

#### **INGREDIENTS**

- |     | <b>Ingredient Name</b>           | <b>CAS Number</b> | <b>%</b> |
|-----|----------------------------------|-------------------|----------|
| 2a. | Copolymer of Ethylene and Octene | 026221-73-8       | ≤ 99.0%  |
|     | Product Stabilizers and Colorant | Mixture           | ≤ 1.0%   |
- 

### **SECTION 3 - HAZARD INFORMATION**

CAUTION! PLASTIC BAG OR LINER MAY CAUSE STATIC IGNITION HAZARD. DO NOT HANDLE BAGS OR LINERS IN THE PRESENCE OF FLAMMABLE VAPOR. EXPOSURE TO DUST AND PROCESSING FUMES MAY CAUSE IRRITATION OF SKIN, EYES, AND RESPIRATORY TRACT. IT MAY ALSO CAUSE SKIN SENSITIZATION. USE APPROPRIATE SAFETY EQUIPMENT WHEN HANDLING.

THIS PRODUCT IS NOT INTENDED FOR PROLONGED CONTACT WITH MUCOUS MEMBRANES, ABRADED SKIN, BODY FLUIDS, OR IMPLANTATION WITHIN THE HUMAN BODY UNLESS IT HAS BEEN SAFETY TESTED.



Advanced Applications

## Material Safety Data Sheet

Version Number: 1

Page Two  
Raprex™ R-300A1 MSDS  
Effective Date June 2004

- |     |                                   |   |
|-----|-----------------------------------|---|
| 3a. | Effects of acute over exposure:   | Low order of toxicity   |
| 3b. | Effects of chronic over exposure: | Low order of toxicity   |
| 3c. | OSHA permissible exposure limit:  | 5 mg/m <sup>3</sup> respirable dust<br>15 mg/m <sup>3</sup> total dust<br>ACGIH TLV 3 mg/m <sup>3</sup> |
| 3d. | Carcinogen potential:             |   |
|     | OSHA:                             | Not Listed  |
|     | National Toxicology Program:      | Not Listed  |
|     | I.A.R.C. Monograms:               | Not Listed  |

---

### SECTION 4 - EMERGENCY AND FIRST AID PROCEDURES

- |     |             |   |
|-----|-------------|---|
| 4a. | Inhalation: | Move to fresh air if inhaled. In case of irritation of respiratory system or mucous membranes, seek medical attention, If effected person feels unwell, seek medical advice. In case of prolonged exposure, seek medical attention.   |
| 4b. | Eyes:       | Immediately flush from eyes with water for at least 15 minutes; get medical attention.  |
| 4c. | Skin:       | Wash off with soap and water. Do not use organic solvents. Cool skin rapidly if contacted with molten polymer. Obtain medical attention for thermal burns.  |
| 4d. | Ingestion:  | Immediately give plenty (>500 cc) of water. In case of spontaneous vomiting be sure that vomitus can freely drain due to danger of suffocation. Give water repeatedly, Artificial induction of vomiting should be restricted to first aid staff. Give nothing by mouth in case of unconsciousness or convulsion. Seek medical advice. |

---

### SECTION 5 - FIRE AND EXPLOSION DATA

- |     |                                     |  |
|-----|-------------------------------------|--|
| 5a. | Flash point:                        | Not determined   |
| 5b. | Upper Explosive Limit:              | Not determined   |
| 5c. | Lower explosive Limit:              | Not determined   |
| 5d. | Auto ignition temperature:          | Not determined   |
| 5e. | Extinguishing media:                | Dry chemical, water fog, foam, carbon dioxide  |
| 5f. | Special fire and explosion hazards: | Dense smoke emitted when burned without sufficient oxygen. Possible dust explosion if polymer fines accumulate. Be careful of possible static explosion. Wear standard fire fighting attire. |



Advanced Applications

Material Safety Data Sheet

Version Number: 1

Page Three  
Raprex™ R-300A1 MSDS  
Effective Date June 2004

**SECTION 6 - SPILLS AND DISPOSAL**

- 6a. Land Spill: Spilled material should be swept up and discarded. Use care as the pellets are extremely slippery. Comply with applicable federal, state or local regulations.
- 6b. Water Spill: Advise local authorities if spilled in waterway or sewer. Skim from surface of water if possible.
- 6c. Waste disposal: Dispose in accordance with local and federal regulations

**SECTION 7 - STORAGE AND HANDLING**

Inspect handling system regularly for possible accumulation of polymer fines. Polymer fines can present an explosion hazard when exposed to heat, sparks or flames. Ventilate before unloading to prevent possible explosion hazard. Use proper grounding procedures.

**SECTION 8 - PROTECTIVE MEASURES**

Wear safety glasses, face shield or chemical goggles to avoid getting material in the eyes during handling.

Wear protective sleeves and face shield when processing material at elevated temperatures to minimize possibility of thermal burns.

Adequate ventilation is recommended to minimize accumulation of polymer fines or vapors during processing and handling. A NIOSH approved respirator may be needed in areas with a high accumulation of fines.

**SECTION 9 - PHYSICAL DATA**

- 9a. Appearance and Odor: Odorless/ colorless or white to off-white pellets
- 9b. Boiling Point: Not applicable
- 9c. Solubility: Insoluble in Water
- 9d. Evaporation: Not applicable
- 9e. Specific Gravity: 0.910 to 0.930 g/cm<sup>3</sup> @23° C
- 9f. Vapor Pressure: Not Applicable
- 9g. Melting Point: Not determined
- 9h. Vapor Density: Not Applicable
- 9i. Percent Volatile: Negligible



Advanced Applications

## Material Safety Data Sheet

Version Number: 1

Page Four  
Raprex™ R-300A1 MSDS  
Effective Date June 2004

### SECTION 10 - REACTIVITY

- 10a. Stability: The material is stable.
- 10b. Hazardous Polymerization: Hazardous Polymerization will not occur.
- 10c. Conditions to avoid: Avoid temperatures over 650° F. Avoid storage or contact with strong oxidizing agents.
- 10d. Combustion Products: The following combustion products may be generated: carbon dioxide, carbon monoxide, water vapor, and trace volatile organic compounds.

---

### SECTION 11 - ADDITIONAL REGULATORY INFORMATION

This material is not regulated by US Department of Transportation.

TSCA Classification: Listed or Exempt.

This material does not contain any chemicals subject to Section 12(b)-US Export Notification.

This material is not subject to specific CERCLA reporting requirements.

This material is not subject to SARA 313 reporting requirements.

This material is subject to California Safe Drinking Water and Toxic Enforcement Act (Proposition 65) reporting.

---

### SECTION 12 - MISCELLANEOUS INFORMATION

TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED HEREIN IS ACCURATE. NEITHER STERIGENICS NOR ANY OF ITS AFFILIATES MAKES ANY WARRANTY, EXPRESS OR IMPLIED, OR ACCEPTS ANY LIABILITY IN CONNECTION WITH THIS INFORMATION OR ITS USE. THIS INFORMATION IS FOR USE BY QUALIFIED EXPERTS AT THEIR OWN DISCRETION AND RISK AND DOES NOT RELATE TO THE USE OF THIS PRODUCT IN COMBINATION WITH ANY OTHER SUBSTANCE OR ANY OTHER PROCESS. THIS IS NOT A LICENSE UNDER ANY PATENT OR OTHER PROPRIETARY RIGHT. THE USER MUST DETERMINE SUITABILITY OF ANY INFORMATION OR MATERIAL FOR ANY CONTEMPLATED USE, THE MANNER OF USE AND WHETHER ANY PATENTS ARE INFRINGED. NO SPECIFICATION FOR THE MATERIALS SHALL BE A WARRANTY, EXPRESS OR IMPLIED, AGAINST ANY CLAIMS FOR INFRINGEMENT OF PATENTS, COPYRIGHTS, TRADEMARKS, OR SIMILAR MATTERS. THERE ARE NO WARRANTIES WHICH EXTEND BEYOND THE DESCRIPTION OF THE MATERIALS SOLD. STERIGENICS MAKES NO WARRANTY THAT THE MATERIALS SOLD SHALL BE MERCHANTABLE OR FIT FOR ANY PARTICULAR PURPOSE. NO WARRANTY OF ANY KIND, IMPLIED OR EXPRESS, IS GIVEN BY STERIGENICS, AND SPECIFICALLY THAT NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR PURPOSE IS GIVEN. IN NO EVENT SHALL STERIGENICS BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL, PUNITIVE OR OTHER SIMILAR DAMAGES, INCLUDING BUT NOT LIMITED TO DAMAGES ARISING FROM DEATH, BODILY INJURY, PROPERTY DAMAGE, LOSS OF PROFITS OR REVENUE OR LOSS OF USE OF THE MATERIALS.